



Hydro-Extractors
P.O. Box 1027
Beaumont, Texas 77704
Phone: 409-926-6326
Email: hydroextractors@gmail.com

SPECIFICATIONS FOR MODEL 2020 EXTRACTOR

Approximate Dimensions:

Extractor Length	22 Ft. 6 In.
Extractor Width	4 Ft.
Height in Load Position	9 Ft. 7 In.
Weight of Extractor	12,500 Lbs.

Capacity

Exchanger Tube Sheet Diameter (This is the standard model; we have different options that will enable the extractor to pull larger diameter exchangers.)	66 In. Dia.
Length of Free Pull	20 Ft.
Force Applied With Main Hydraulic pull motors	120,000 Lbs.
Weight Capacity of Extractor - non shock	60,000 Lbs.
Pull Speed	6 Ft. /Min.

HYDRAULIC SYSTEM

Drive Motor - 33 H.P. @ 3,000 RPM air Cooled Diesel Engine, w/Spark Arrester

Pump System – 0.51 CIR gear pump

- Inline Suction Filter - 25 Micron

Hydraulic Oil Reservoir - 15 Gallon Capacity

Diesel Fuel Reservoir - 15 Gallon Capacity

Piping - S.S. Suction & Discharge Lines

- Hydraulic Hose to Component Parts

Control Valves – Remote Miritron five function WIRELESS REMOTE with 15' of tether line

Cylinders

- 5,000-PSI non-shock with controlled rods.
- (Optional) remote control for all hydraulic functions on diesel driven units only.
- (Optional) remote, for control of only the main hydraulic cylinder. (Air or diesel)