



Hydro-Extractors
P.O. Box 1027
Beaumont, Texas 77704
Phone:409-926-6326
Email: hydroextractors@gmail.com

SPECIFICATIONS FOR MODEL 504 -20' EXTRACTOR

Approximate Dimensions:

Extractor Length	27 Ft. 2 In.
Extractor Width	6 Ft.
Height in Load Position	8 Ft.
Weight of Extractor	14,000 Lbs.

Capacity

Exchanger Tube Sheet Diameter (This is the standard model; we have different options that will enable the extractor to pull larger diameter exchangers.)	66 In. Dia.
Length of Free Pull	21 Ft. 6 In.
Force Applied With Main Cylinder @ 3,000 PSI	113,100 Lbs.
(Optional) Force Applied With Main Cylinder @ 5,000 PSI	189,000 Lbs.
Force Applied With Chain Motors @ 3,000 PSI	13,000 Lbs.
Weight Capacity of Extractor - non shock	60,000 Lbs.
Pull Speed with Main Cylinder	6 Ft. /Min.
Pull Speed With Chain Motors	20 Ft.

	/Min.
--	-------

HYDRAULIC SYSTEM

- Drive Motor** - 18 H.P. Piston Type Air Motor @ 90 PSI / 450 CFM
(Optional) - 35.9 H.P. @ 3,000 RPM Water Cooled Diesel Engine w/Spark Arrester

Pump System

- Tandem Pumps With Total Capacity 29 GPM
- Volume - Low Pressure Pump - 22 GPM @ 1,000 PSIG
- High Pressure Pump - 7 GPM @ 3,000 PSIG
- Automatic Unloading @ 1,000 PSIG
- Inline Suction Filter - 25 Micron

Reservoir

- 40 Gallon Capacity - 1/8" Type 304 S.S. Plate

Piping

- S.S. Suction & Discharge Lines
- Hydraulic Hose to Component Parts

Control Valves

- Manual, 4-Way Spool Type

Cylinders

- 5,000-PSI non-shock with controlled rods.
- (Optional) remote control for all hydraulic functions on diesel driven units only.
- (Optional) remote, for control of only the main hydraulic cylinder. (Air or diesel)